




## Declaration of Performance

According to REGULATION EU CPR No 305/2011 and 275/2013 government decree

|   |  |  |              |
|---|--|--|--------------|
| <b>1. Manufacturer::</b>  | <b>Tompa Ingatlanforgalmi Kft.</b>                           |  |              |
| <b>2. Aggregate Type / Description:</b>   | 0-4  |  |              |
| <b>3. Unique Identification code of the product - type::</b>  | TLI TK-1/2020  |  |              |
| <b>4. Intened use:</b>  | <b>Aggregates for concrete</b>                               |  |              |
| <b>5. Harmonised Standard:</b>  | <b>MSZ EN 12620 -2006</b>                                    |  |              |
| <b>6. System of AVCP:</b>   | 2+   |  |              |
| <b>7. Certificate number of FPC:</b>  | 2095 CPR 218   |  |              |
| <b>8. Notified body:</b>  | TLI Technológiai, Laboratóriumi és Innovációs Zrt. (NB 2095) |  |              |
| <b>9. Declared Performances:</b>  |  |  |              |
| <b>Requirement</b>  | <b>Test standard</b>   | <b>Sign</b>  | <b>Class</b> |
| <b>Geometric requirements</b>   |  |  |              |
| Oven-dried particle density   | MSZ EN 1097-6: 2013  | Mg/m <sup>3</sup>  | fine 2,61    |
| Particle Size   | MSZ EN 933-1: 2012 fine                                      | 0-4  | GF85         |
| Water absorption  | MSZ EN 1097-6: 2013  | WA24   | 2,00%        |
| Fines content   | MSZ EN 933-1:2012  | f  | f3           |
| Assessment of fines   | MSZ EN12620 "D" EN 933-9<br>Methylene blue test              | MBF  | NPD          |
| Volumetric sedimentation study of sludge clay content   | MSZ 18288/2-1984 9.  | %  | 1,3          |
| <b>Physical requirements</b>  |  |  |              |
| Resistance to fragmentation/crushing  | MSZ EN 1097-2:1988 5.  | LA   | LA25         |
| Resistance to wear  | MSZ EN 1097-1: 2012  | MDE  | MDE10        |
| Durability against freeze/thaw  | MSZ EN 1367-1: 2007  | MS   | F1           |
| Durability against alkali-silica reactivity   | MÉASZ ASTM C 289-87  |  | NPD          |
| Drying shrinkage  | MSZ EN 1367-4: 2000  |  | NPD          |
| <b>Chemical requirements</b>  |  |  |              |
| Chemical composition  | MSZ EN 932-3: 1998   |  | NPD          |
| Shell Content   | MSZ EN 933-1: 2012   |  | NPD          |
| Chlorides   | MSZ EN 1744-1:1998 7.  |  | NPD          |
| Acid soluble sulfate  | MSZ EN 1744-1: 1998 12.                                      |  | NPD          |
| Total sulphur   | MSZ EN 1744-1:1998 11.                                       |  | NPD          |
| <b>10. Declaration:</b> The performance of the product specified in points 2 corresponds to the performance indicated in point 9. This declaration of performance is the sole responsibility of the manufacturer as specified in point 1.   |  |  |              |
| <b>11. Conditions for the validity of the declaration of performance:</b>   |  |  |              |
| The supplier is responsible for ensuring the cleanliness of the transport vehicle and the transport of the product without contamination. The product maintains the performance stated above when transported on a closed surface with a clean surface. In the event of a quality complaint, the supplier must certify that no event has occurred during the delivery that could affect the performance of the product. Quality complaints arising from transport, storage and handling do not affect the manufacturer's liability. |  |  |              |
| Signed for and on behalf of the manufacturer by::   |  |  |              |
| Szalkszentmárton, 26.10.2020.   |  | <br><b>„TOMPA” Ingatlanforgalmi Korlátolt Felelősségű Társaság</b><br>0800 Nagykanizsa, Magyar u. 14.<br>Adószám: 13348425-2-20<br>14100134-40227149-01000000 |              |
|   |  | Tompa Ferenc<br>Plant manager  |              |
| Environmental, health and safety information (REACH): The product is not dangerous according to the relevant Decree 44/2000 (XII. 27.) EüM.   |  |  |              |
| <b>Legal information: Complaints to the manufacturer can be validated on the basis of the invoice, delivery note and this declaration for the product!</b>  |  |  |              |
| The manufacturer shall keep the declaration and the accompanying certificates of conformity for a period of 10 years after the date of issue.   |  |  |              |